


Mako Marine Fuel Filler USCG/SAE J1527 Type A1 Flame Retardant



Recommended Usages:

Type A1 fuel fill hose is constructed with high grade chemigum tube for superior fuel resistance for type A1 fuel fill applications. This is the connection from the boats fuel fill port down to the boats fuel tanks.

USCG/SAE J1527 Type A1 unleaded resistant.

Cover: Flame Retardant

Reinforcement: Two-ply synthetic braid with wire helix.

Tube: Black Nitrile

Temperature Range:

-30°C to 90°C

Recommended Usages:



Fuel feed & vent applications on marine pleasure crafts. This hose meets or exceeds US Coast Guard requirements for type A1 services as outlined SAE J1527

Cover:

Flame Retardant Synthetic Rubber

Reinforcement:

Synthetic Braid

Tube:

Black Nitrile

Temperature Range:

-30° to 90° C

| Product Code | I.D. mm | O.D. mm | W.P PSI | Coil/ MT |
|----------------|---------|---------|---------|----------|
| MFF-020 | 19 | 29.4 | 100 | 20 |
| MFF-025 | 25 | 38.1 | 100 | 20 |
| MFF-032 | 32 | 47.3 | 100 | 20 |
| MFF-040 | 38 | 47.1 | 100 | 20 |
| MFF-050 | 51 | 61.5 | 50 | 20 |

Mako Marine Fuel Line USCG/SAE J1527 Type A1

| Product Code | I.D. mm | O.D. mm | W.P PSI | Coil/ MT |
|----------------|---------|---------|---------|----------|
| MRF-006 | 6 | 16.5 | 50 | 30 |
| MRF-008 | 8 | 18 | 50 | 30 |
| MRF-010 | 10 | 19.8 | 50 | 30 |
| MRF-012 | 12 | 22.8 | 43 | 30 |
| MRF-016 | 16 | 25.8 | 43 | 30 |
| MRF-020 | 19 | 28 | 43 | 30 |

Mako Red Multipurpose



Recommended Usages:

This high quality multipurpose hose is suitable for conveying air, water, oil, all alcohol blended fuel & all petroleum based products.

Cover: Red non-conductive ozone weather & oil resistant

Reinforcement: Braided synthetic cord

Tube: Black smooth 50% aromatic Nitrile tube

| Product Code | I.D. mm | O.D. mm | W.P PSI | Coil/ MT |
|----------------|---------|---------|---------|----------|
| E08-005 | 4.8 | 12 | 290 | 200 |
| E08-006 | 6.4 | 13 | 290 | 200 |
| E08-008 | 7.9 | 15 | 290 | 200 |
| E08-010 | 9.5 | 17 | 290 | 200 |
| E08-012 | 12.7 | 21 | 290 | 152 |
| E08-016 | 15.8 | 26 | 290 | 152 |
| E08-020 | 19.1 | 29 | 290 | 152 |
| E08-025 | 25.4 | 36 | 290 | 152 |
| E08-032 | 31.4 | 44 | 290 | 60 |
| E08-038 | 38.1 | 54 | 290 | 60 |
| E08-050 | 50.8 | 67 | 290 | 60 |

Temperature Range:

-25°C to 95°C

4:1 Safety Factor

Hydraulic Crimping Service Now Available

In-house Hydraulic & Industrial Crimping.

We carry Gate Hydraulic Hose & a range of Crimp fittings to suit.

Also available JIC, BSPT, BSPP &

UNO, Metric Light & Heavy fittings

Crimp range 1/4" - 6"

