

MAKO MARINE FUEL LINE B1

J1527 TYPE B1

Construction

Cover:

Fire Resistant

Reinforcement:

Synthetic Braid

Tube:

Black nitrile to USCG standard

Recommended For:

This hose provides flexible connections between rigid fuel distribution lines and engine where the hose is in an open environment on pleasure craft. This is suitable for marine diesel and gasoline blends of ethanol, methanol and ethers up to 15%. Not suitable for below floor applications.

Temperature Range:

-20°C to 70°C

NOT SUITABLE FOR CONFINED SPACES



Product Code	I.D. (mm)	O.D. (mm)	Working Pressure (bar)	Burst Pressure (bar)	Roll Length (mt)
MBF-008	7.9	14.3	3.5	14	30
MBF-010	9.5	15.8	3.5	14	30

**Formerly MRFB*

E07 - BLUE FORTRESS 300 WITH MICROBAN®

NITRILE SYNTHETIC RUBBER HOSE

Continental FORTRESS® 300 with MICROBAN® MADE IN USA

Product Code	I.D. (in)	I.D. (mm)	O.D. (mm)	Working Pressure (psi)	Weight (kg/m)	Roll Length (mt)
E07-012	1/2	12	22.8	300	0.45	152.4
E07-020	3/4	19	30.2	300	0.65	152.4
E07-025	1	25	38.1	300	0.95	137.2

Application:

A high-quality construction for hot water up to 200°F (99°C) cleanup service in food processing plants, dairies, packing houses, bottling plants, breweries, canneries and creameries. Its super abrasion and oil-resistant cover provides maximum protection against the adverse effects of oil and animal fats. The cover of our Blue Fortress' 300 hose incorporates Microban's® antimicrobial built-in product protection. The white tube is comprised of FDA compliant materials.

Construction Tube:

White FDA compliant Nitrile synthetic rubber.

Cover:

Blue Carbryn™ synthetic rubber, RMA Class A (High Oil Resistance) with Microban® product protection.

Reinforcement:

Spiral synthetic yarn.

Temperature Range:

-29°C to 99°C

Branding:

Example: Fortress® 300 with Microban® Antimicrobial Product Protection 3/4" 300 psi WP. Made in USA. Continental ContiTech®

Safety Factor:

4:1

RUBBER HOSE

M04 - WATER DISCHARGE HOSE (MANDREL TYPE)



Construction

Core

Black, smooth, synthetic rubber.

Reinforcement

High strength synthetic cord.

Cover

Black, smooth (wrapped finish), synthetic rubber, weathering and ozone resistant.

Application

Softwall hose designed for water, and non-corrosive fluids used in construction sites and light duty industrial applications.

Temperature Range:

-20°C to +70°C

Product Code	I.D. (mm)	O.D. (mm)	Working Pressure (psi)	Working Pressure (bar)	Burst Pressure (psi)	Burst Pressure (bar)	Roll Length (mt)
M04-012	12.7	21	150	10	450	30	20, 60
M04-020	19.1	28	150	10	450	30	20, 60
M04-025	25.4	34	150	10	450	30	20, 60
M04-032	31.8	42	150	10	450	30	20, 60
M04-038	38.1	48	150	10	450	30	20, 60
M04-050	50.8	62	150	10	450	30	20, 60
M04-065	63.5	76	150	10	450	30	20, 60
M04-075	76.2	89	150	10	450	30	20, 60
M04-100	101.6	116	150	10	450	30	20, 60
M04-114	114.3	129	150	10	450	30	20, 60
M04-125	127	142	150	10	450	30	20, 60
M04-150	152.4	167	150	10	450	30	20, 60

HOSE VARIOUS

M05 - 40 BAR STEEL AIR DELIVERY HOSE



Application

Heavy-duty compressed air delivery hose designed for severe service conditions including mining, quarrying, construction, and industrial environments. Suitable for high-pressure air transfer where durability and reliability are critical.

Construction

Tube: Black synthetic rubber, resistant to compressed air

Reinforcement: Single high-tensile steel wire braid

Cover: Yellow synthetic rubber, resistant to water, abrasion, and harsh environments

Key Features

- High-pressure rating: 40 Bar (580 PSI)
- Excellent resistance to tough working conditions
- Durable, abrasion-resistant outer cover
- Flexible and easy to handle under pressure
- Suitable for rugged industrial applications

Temperature Range

-40°C to +90°C

Product Code	I.D. (in)	I.D. (mm)	O.D. (mm)	Working Pressure (psi)	Working Pressure (bar)	Burst Pressure (psi)	Burst Pressure (bar)	Bend Radius (mm)	Weight (kg/m)	Roll Length (mt)
M05-038	1½	38.7	51.7	580	40	1740	120	500	1.5	20, 60
M05-050	2	51.3	63	580	40	1740	120	630	2	20, 60
M05-075	3	76.2	95	580	40	1740	120	915	5.3	20, 60

BARFELL ESTATE BLULINE

PVC PRESSURE HOSE



Colour:

Inner wall: Black
Outer wall: Smooth White with Blue Stripes

Application:

All commercial parks, gardens and turf watering applications. Ideal as a general cold water wash down hose in cattle yards and dairies.

Description:

Highly flexible premium hose for watering parks and gardens. With high visibility and two distinctive blue stripes, it is kink, burst and UV light resistant.

Product Code	I.D. (mm)	O.D. (mm)	Working Pressure @ 20°C (psi)	Burst Pressure @ 20°C (psi)	Weight (kg/m)	Roll Length (mt)
A55-012	12.5	19	145	580	0.22	20, 100
A55-020	19	26.5	145	580	0.4	20, 30, 100
A55-025	25	34	145	580	0.58	20, 30, 100
A55-032	31.5	42	145	580	0.85	20, 30, 100
A55-038	38	49.5	145	580	1.11	20, 30, 60

BARFELL HOT WASH WHITE

PVC PRESSURE HOSE



Colour:

Inner wall: White
Outer wall: White with smooth TPR surface

Rated to 85°C when used at low pressure.

Application:

Hot washdown of all food preparation and retail areas, where milk, fats and other food products are present.

Description:

Highest grade hose for hot washdown use in the food industry. The thermoplastic rubber smooth outer cover is highly resistant to lactic acid and fats.

Product Code	I.D. (mm)	O.D. (mm)	Working Pressure @ 20°C (psi)	Burst Pressure @ 20°C (psi)	Weight (kg/m)	Roll Length (mt)
A08-012	12.5	19.7	290	1,160	0.28	20, 100
A08-020	19	28	250	1,000	0.48	20, 100

BARFELL FRAS PVC PRESSURE HOSE



Colour:

Inner wall: Black
 Outer wall: Ribbed Yellow with Black Stripe.

Application:

Underground air and water mining hose.

Description:

Fire resistant anti static hose with unique 3 layer construction that offers optimum performance and handling characteristics.

Manufactured to AS2660 Class A (1991) and AS/NZ2554 Class A.

Product Code	I.D. (mm)	O.D. (mm)	Working Pressure @ 20°C (psi)	Burst Pressure @ 20°C (psi)	Weight (kg/m)	Roll Length (mt)
A40-010	10	18	305	1,200	0.25	20, 100
A40-012	12.5	20.9	305	1,200	0.26	20, 30, 100
A40-020	20	29.4	305	1,200	0.58	20, 30, 100
A40-025	25	34.8	305	1,200	0.71	20, 30, 100
A40-038	38	48.8	305	1,200	1.19	20, 150, 200
A40-050	50	62.4	305	1,200	1.8	20, 100, 200

B51HD HEAVY DUTY STATIC DISSIPATING ABRASIVE SUCTION POLYURETHANE / PVC HOSE



Product Code	I.D. (in)	I.D. (mm)	O.D. (mm)	Working Pressure (psi)	Working Pressure (bar)	Bend Radius (mm)	Weight (kg/m)	Roll Length (mt)
B51-050HD	2	50.8	61.2	50	3.4	102	0.51	30
B51-065HD	2½	63.7	76.2	50	3.4	127	0.74	30
B51-075HD	3	76	88.9	45	3.1	152	1.01	30
B51-100HD	4	102.2	116.3	40	2.7	229	1.32	30
B51-125HD	5	127	170.2	23	1.5	381	2	30
B51-150HD	6	152.4	200	20	1.3	450	3.37	30

Application

Heavy duty liquid suction and discharge
 Suitable for liquid waste handling, septic and cesspool cleaning
 Ideal for construction, agricultural and marine applications

Construction Tube

Thick SBR rubber tube with PVC helix reinforcement
 Smooth bore for efficient flow
 Smooth exterior for easy handling and cleaning
 High working pressure capability
 Excellent resistance to cold weather conditions
 Blue inner liner

Temperature Range

-40°C to +60°C

Branding

Not branded

Vacuum Rating (in Hg)

29.8