BLACK TPR DUCT

Colour: Black.

Temperature: -40°C to 125°C

Features: Thermoplastic rubber with wire helix reinforcement. Good abrasive qualities and U.V. resistance.

Application: General purpose ducting for use over a variety of temperatures.

Product Code	I.D. (in)	I.D. (mm)	Bend Radius (mm)	Roll Length (mt)
J16-038	1½"	38	30	10, 20
J16-050	2"	51	40	10, 20
J16-063	2½"	63	55	10, 20
J16-075	3"	76	65	10, 20
J16-100	4"	102	85	10, 20
J16-125	5"	127	105	10, 20
J16-150	6"	152	125	10, 20
J16-200	8"	203	165	10, 20
J16-230	9"	228	185	10, 20
J16-250	10"	255	210	10, 20
J16-280	11"	279	230	10, 20
J16-300	12"	305	250	10, 20
J16-350	14"	356	300	10, 20
J16-400	16"	406	350	10, 20

CLEAR POLYURETHANE DUCT

Colour: Clear with copper plated steel wire.

Temperature: -40°C to 90°C

Features: Polyurethane ducting with coppered steel wire. Very flexible and light featuring high abrasion resistance and flexbility. Weather resistance and suitable for most chemicals.

Application: Suction and discharge of abrasive powders, fumes, shavings etc. Used when flexibility is required.

Product Code	I.D. (in)	I.D. (mm)	Bend Radius (mm)	Weight (kg/m)	Roll Length (mt)
J17-038	1½"	38	30	0.17	10, 20
J17-050	2"	51	40	0.22	10, 20
J17-063	2½"	63	55	0.27	10, 20
J17-075	3"	76	65	0.4	10, 20
J17-100	4"	102	85	0.53	10, 20
J17-125	5"	127	105	0.63	10, 20
J17-150	6"	152	125	0.89	10, 20
J17-180	7"	180	150	1.25	10, 20
J17-200	8"	203	165	1.4	10, 20
J17-230	9"	228	185	1.57	10, 20
J17-250	10"	254	210	1.9	10, 20
J17-300	12"	305	230	2.28	10, 20

CLEAR POLYURETHANE SMOOTH BORE ANTI-STATIC CLEAR DUCT

Colour: Clear transparent with white spiral, anti-static wire externally.

Temperature: -40°C to 80°C

Features: PU hose reinforced with anti-shock rigid PVC spiral. Outside surface is corrugated, with smooth inside surface. Light and flexible hose with a high resistance against abrasion and bending. Weather resistant and suitable for most chemicals.

Application: Suction and discharge of abrasive powders, fumes, shavings etc for heavy duty industrial and abrasive applications.

Product Code	I.D. (in)	I.D. (mm)	Bend Radius (mm)	Weight (kg/m)	Roll Length (mt)
J11-032	1¼"	32	35	0.23	10, 20
J11-038	1½"	38	50	0.25	10, 20
J11-050	2"	51	70	0.36	10, 20
J11-063	2½"	63	80	0.54	10, 20
J11-075	3"	76	100	0.63	10, 20
J11-100	4"	102	140	0.83	10, 20
J11-125	5"	127	170	1.2	10, 20
J11-150	6"	152	200	1.61	10, 20
J11-180	7"	180	250	2.1	10, 20
J11-200	8"	203	260	2.33	10, 20
J11-250	10"	254	300	2.65	10, 20
J11-300	12"	305	350	3.45	10, 20

GREY FLAME RESISTANT DUCT

Colour: Grey.

Temperature: -20°C to100°C

Features: Flexible flame resistant ducting made from a textile fabric with PVC coating, reinforced with a steel helix welded between the two fabric layers.

Application: Civil and naval conditioning plants, ventilation systems, suction of fumes, smokes, gases and powders.

Product Code	I.D. (in)	I.D. (mm)	Bend Radius (mm)	Weight (kg/m)	Roll Length (mt)
J13-050	2"	51	26	0.12	10, 20
J13-063	2.1/2"	63	30	0.14	10, 20
J13-075	3"	76	38	0.18	10, 20
J13-100	4"	102	51	0.28	10, 20
J13-125	5"	127	64	0.38	10, 20
J13-150	6"	152	76	0.41	10, 20
J13-200	8"	203	102	0.57	10, 20
J13-250	10"	254	127	0.8	10, 20
J13-300	12"	305	153	0.96	10, 20
J13-350	14"	356	138	1.11	10, 20
J13-400	16"	406	165	1.27	10, 20